



Phormium

Supporting growers since 1977

PHL 20

Energy saving gable screen

Technical data sheet

Product description

Type of product	Laminated woven fabric	Application	Indoor
Colour	Diffuse	Material	100% Polyethylene

Properties

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	91 g/m ²	±9,1 g/m ²
Length		As required	-
Roll Width		190-210-230-250-270 cm	±2 cm
		74,8-82,7-90,5-98,4-106,3 in	±0,8 in

Mechanical Properties	Standard	Performance
Energy saving	Phormium test method	50 %
Direct Light transmission	Phormium test method	84 %
Shading	Phormium test method	16 %
Shrinkage	2h at 70°C	≤1 %

Durability	Standard	Performance
Flame retardant	DIN 4102	-
	NTA 8825	-
	ASTM E 84	-
	NFPA 701 - 2015 Test Method 2	-

Warranty

Under all types of greenhouse covering 8 years, see Phormiums limited warranty for all terms, conditions, and exclusions in writing.

Remarks

The Quality Management System of IFG Cresco has been approved to the ISO 9001 / ISO 14001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.



BQA_QMS_C_2017734



BQA_QMS_C_2020734



019 - QMS



019 - EMS

IFG Cresco, a division of IFG Exelto N.V.

Weverlaan 15, 9160 Lokeren, Belgium

info@phormium.com / www.phormium.com